P6 P8 **BP15** BP20



Backpack

Sprayers
Supreme for larger areas

BP 15 and PB 20

HARDI 15 and 20 litre Backpack sprayers feature a leak proof tank design with piston pump for easy cleaning and maintenance.

With pressure up to 3 bar, they are ideal for insecticides, fungicides and herbicides. The Controlled Fluid Valve can be used for spraying herbicides. It only sprays at 1 bar, thus ensuring correct pressure for the herbicide nozzles.

The tank is not pressurized. Spraying is controlled from the trigger valve.

The sprayers comprise of few parts with no special tools needed for maintenance. A graduated 250 ml measuring jug is standard.



HARDI BP15 and BP20 features

- 1. Herbicide and insecticide/ fungicide nozzles supplied
- 2. CF Valve for accurate 1 bar herbicide spraying (option)
- 3. Lance holder for tidy storage
- 4. Carry grip for easy handling
- **5.** Spring-loaded, ON/OFF valve on a lightweight 50 cm lance
- **6.** Filter to minimize nozzle blockage
- 7. Reusable hose clips
- **8.** Reinforced, 124 cm synthetic hose with 60 bar burst pressure

- 9. Quick filling and tank access with large 12.4 cm opening
- **10.** Angled, sided-located opening for complete emptying of the tank
- **11.** Transparent, polypropylene tank with moulded indicator for accuracy
- 12. High capacity basket strainer to reduce pump wear
- **13.** Left or right-handed operation of the pump lever
- 14. Ergonomic design for working comfort and less back strain
- 15. Comfortable 6 x 20 cm nonabsorbent shoulder pads
- **16.** Easy to adjust shoulder harness
- 17. Waist belt with snap buckle to prevent side movement
- **18.** Storage for nozzles etc
- 19. Leak-proof tank; all holes are at the top







Efficient

2 www.hardi-international.com

Pressure sprayers

Ideal under difficult conditions

HARDI P1.5, P6 and P8

HARDI P1.5, P6 and P8 pressure sprayers are compact, easy to use and built for professional pesticide application. Capacity is 1.5, 6 or 8 litres.

To spray, the pump is used to pressurize the tank. Spraying is controlled from the trigger valve.

All seals are of highly resistant material and tolerate most mineral-based products.

The P1.5 spray can be adjusted from 45° cone spray to solid stream. Maximum reach is 5 m.

Spray quality is from a fine mist to coarse drops. Over-pressurizing the tank is not possible.







HARDI P1.5, P6 and P8 features

- **1.** Highly resistant seals (Viton)
- **2.** Carry strap does not absorb pesticide
- **3.** Angled, sided-located 8 cm opening for complete emptying
- **4.** Two carry methods; handle or strap
- **5.** Spring-loaded, quick acting ON/OFF valve
- **6.** Filter to minimize nozzle blockage
- **7.** Lance holder for tidy storage
- **8.** Leakproof tank, all holes are at the top
- **9.** Transparent, polypropylene tank
- **10.** Easy to service pump barrel
- **11.** Strong, lightweight 37 or 50 cm lance

- **12.** Reinforced, 124 cm synthetic hose with 60 bar burst pressure
- **13.** Valve to decompress tank and prevent overpressurization (3 bar maximum)
- **14.** Herbicide and insecticide/ fungicide nozzles supplied
- **15.** Measuring jug (2 to 40 ml) incorporated in lid for minimal residues
- **16.** Graduation of 250 and 500 ml inside tank
- 17. Storage for extra nozzles
- **18.** Suction filter to prevent nozzle blockage
- **19.** Graduations of 250 ml on tank
- **20.** Wear resistant ceramic nozzle









HARDI

The Sprayer

HARDI INTERNATIONAL A/S

is an international group whose basic idea is to satisfy the user's requirements for quality products which ensure efficient, punctual and precise application of crop protection products. Our world-wide distribution and sales network comprise of more than 100 countries where we are represented by importers, agents and sales subsidiaries. These are situated in Sweden, Norway, Denmark, France, Spain, North America, Australia. China and EMC — Russia & CIS countries.

Since 1957 HARDI has committed to the ever-increasing demands for efficient and precise plant protection. HARDI is the trendsetter within application of crop protection products. To achieve this position continued developments and innovation are essential. HARDI is committed to the long term future of plant protection.

Optional extras



Telescopic lancesA compact extension for tall targets. Available from 0.5 m to 2.0 m.



Spray shields
To avoid spray drift.
0.4 m and 0.2 m.



Booms
Ideal for larger areas.
1.0 m, 1.5 m and 2.0 m.



Adjustable nozzle Spray angle, reach and spray quality can quickly be changed. 0.88 to 1.65 l/min.



Lance extensions
Ideal for distant targets
like trees. Available
1 m and 2 m.



Nozzle filtersFitted just prior to the nozzle.

- ▶ Blue = Coarse
- ▶ Red = Medium
- Yellow = Fine



Double nozzle holder For higher volumes of fine spray.



Operator Safety Kit Five Nitril gloves

- Two Coverall (XL) Type 5 (Particle-tight) & Type 6
- Face Shield
- Mask with 3M Gas & Vapour Respirators

Technical specifications

Model	Rated fill litre	Total fill litre	Pressure max bar	Measurements Package cm	Weight kg
BP20	20	22	3	63 x 19 x 41	5.5
BP15	15	16	3	63 x 17 x 39	5.2
P8	8	12	3	69 x 20 x 25	2.4
P5	6	8	3	52 x 20 x 25	1.9
P1.5	1.5	1.9	3	30 x 40 x 29	2.8*

*6 units in package



HARDI INTERNATIONAL A/S

